

WHAT IS CLAIMED IS:

1 1. A method of anchoring a balloon catheter in a patient, comprising the  
2 steps of:  
3 providing a balloon catheter having a shaft and a balloon mounted to  
4 the shaft, the shaft having a distal end and a proximal end, the balloon having  
5 an expanded shape and a collapsed shape, the expanded shape being  
6 configured to occlude a body passageway in a patient, the balloon including  
7 an outer surface having at least two high friction portion and at least two low  
8 friction portions, the low friction portion having a lower coefficient of friction  
9 than the at least two high friction portions relative to the patient's body  
10 passageway, the balloon having at least three radially extending arms when  
11 in the collapsed shape, each of the at least two low friction portions being  
12 positioned at radially outward extremes of adjacent radially extending arms,  
13 the high friction portion being exposed and positioned between the radially  
14 outward extremes of the adjacent radially extending arms when the balloon is  
15 in the collapsed shape, the high friction portion being everted when the  
16 balloon moves from the collapsed shape to the expanded shape;  
17 positioning the balloon in the patient's body passageway with the  
18 balloon in the collapsed shape so that the radially outward extremes contact  
19 the body passageway; and  
20 advancing the balloon in the patient to a position to be occluded with  
21 the balloon in the collapsed shape;  
22 inflating the balloon after the advancing step so that the high friction  
23 portion contacts the patient's body passageway for anchoring the balloon in  
24 the patient's body passageway.

1 2. The method of claim 1, wherein:  
2 the positioning step is carried out by inserting the balloon into the  
3 patient's arterial system; and  
4 the inflating step is carried out with the balloon being positioned in the  
5 patient's ascending aorta.

1 3. The method of claim 1, wherein:  
2 the providing step is carried out with the balloon catheter having a first  
3 lumen and an opening at the distal end fluidly coupled to the first lumen, the  
4 opening being configured for delivery of a fluid into a patient,

1 4. The method of claim 3, further comprising the step of:  
2 introducing cardioplegic fluid into the patient through the first lumen.

1 5. The method of claim 1, wherein:  
2 the providing step is carried out with the balloon catheter having at  
3 least three arms extending radially outward from the shaft.

1 6. The method of claim 1, wherein:  
2 the providing step is carried out with the high friction portion having a  
3 plurality of ribs.

1 7. The method of claim 1, wherein:  
2 the providing step is carried out with the shaft having a substantially  
3 straight portion and a hooked portion connected to the substantially straight  
4 portion.

1 8. A balloon catheter for occluding a body passageway in a patient,  
2 comprising:  
3 a shaft; and  
4 a balloon mounted to the shaft, the balloon having an expanded shape  
5 and a collapsed shape, the expanded shape being configured to occlude a  
6 body passageway in a patient, the balloon including an outer surface having  
7 at least two high friction portions and a low friction portion, the low friction  
8 portion having a lower coefficient of friction than the high friction portions  
9 relative to the patient's body passageway, the balloon having at least three  
10 radially extending arms when in the collapsed shape, each of the at least two

low friction portions being positioned at radially outward extremes of adjacent radially extending arms, the high friction portion being exposed and being positioned between two of the radially outward extremes of the radially extending arms when the balloon is in the collapsed shape, the high friction portion being everted when the balloon moves from the collapsed shape to the expanded shape.

9. The balloon catheter of claim 8, wherein:  
the balloon is configured and sized to occlude the patient's ascending aorta.

10. The balloon catheter of claim 8, wherein:  
the shaft includes a first lumen and an opening at the distal end fluidly coupled to the first lumen, the opening being configured for delivery of a fluid into a patient.

11. The balloon catheter of claim 8, further comprising:  
a source of cardioplegic fluid fluidly coupled to the first lumen.

12. The balloon catheter of claim 8, wherein:  
the high friction portion includes a plurality of ribs.

13. The balloon catheter of claim 8, wherein:  
the shaft has a substantially straight portion and a hooked portion connected to the substantially straight portion.

14. A method for positioning a balloon in a passageway and occluding the passageway, comprising the steps of:  
providing a catheter having a shaft and a balloon mounted thereto, the balloon having a collapsed shape and an expanded shape;  
inserting the catheter into a body passageway of a patient with the balloon in the collapsed shape;

7 positioning the catheter in a portion of the body passageway for  
8 occluding the portion of the body passageway;  
9 inflating the balloon with a fluid;  
10 monitoring a rate of pressure increase in the balloon with respect to a  
11 fluid volume in the balloon; and  
12 adding an amount of fluid after the rate of pressure increase in the  
13 balloon exceeds a predetermined threshold.

1 15. The method of claim 14, wherein:  
2 the positioning step is carried out by positioning the balloon in the  
3 patient's ascending aorta.

1 16. The method of claim 14, wherein:  
2 the providing step is carried out with the catheter having a lumen  
3 fluidly coupled to the balloon, the catheter also having a pressure sensor and  
4 a pressure sensing alarm, the pressure sensing alarm indicating when the rate  
5 of pressure increase in the balloon exceeds the predetermined threshold.

1 17. The method of claim 14, wherein:  
2 the adding step is carried out with the amount of fluid being a  
3 predetermined volume of fluid.

1 18. The method of claim 14, wherein:  
2 the adding step is carried out by adding the amount of fluid to increase  
3 the pressure in the balloon a predetermined amount.

1 19. A device for pressurizing a balloon catheter, comprising:  
2 a catheter having a shaft and a balloon mounted thereto, the balloon  
3 having a collapsed shape and an expanded shape, the collapsed shape being  
4 configured for advancement within a patient the catheter having a first lumen  
5 fluidly coupled to the balloon for inflating the balloon;

6 a fluid source coupled to the first lumen for inflating the balloon;  
7 a pressure sensor configured to measure a pressure in an interior of the  
8 balloon; and  
9 a pressure monitor coupled to the pressure sensor, the pressure  
10 monitor determining when a rate of pressure increase in the balloon with  
11 respect to an increase in fluid volume in the balloon exceeds a predetermined  
12 threshold.

1 20. The device of claim 19, further comprising:  
2 means for adding a predetermined amount of fluid after the pressure  
3 monitor detects the rate of pressure increase exceeds the predetermined  
4 threshold.

1 21. The device of claim 19, further comprising:  
2 means for increasing the pressure in the balloon a predetermined  
3 amount after the pressure monitor detects the rate of pressure increase  
4 exceeds the predetermined threshold.

1 22. A method of anchoring an occluding member in a patient, comprising  
2 the steps of:  
3 inserting a catheter having an occluding member mounted thereto, the  
4 occluding member having a collapsed shape and an expanded shape;  
5 positioning the occluding member in a body passageway in the patient;  
6 expanding the occluding member to the expanded shape after the  
7 positioning step to thereby occlude the body passageway;  
8 monitoring a pressure exerted on the occluding member on a distal  
9 side and a proximal side of the occluding member; and  
10 determining a difference between the pressure on the distal and  
11 proximal sides of the occluding member.

1 23. The method of claim 22, further comprising the step of:

2 adjusting a pressure on at least one of the distal and proximal sides of  
3 the occluding member.

1 24. The method of claim 22, wherein:  
2 the adjusting step is carried out by adjusting a pressure on the distal  
3 side of the occluding member.

1 25. The method of claim 22, wherein:  
2 the inserting step is carried out with the occluding member being a  
3 balloon.

1 26. The method of claim 22, wherein:  
2 the inserting step is carried out with the body passageway being an  
3 ascending aorta.

1 27. A catheter for occluding an ascending aorta in a patient, comprising:  
2 a shaft having a distal end and a proximal end;  
3 an occluding member mounted to the shaft, the occluding member  
4 having an expanded shape sized to occlude the patient's ascending aorta;  
5 a first pressure sensor positioned between the distal end and the  
6 occluding member for measuring a pressure on a first side of the occluding  
7 member; and  
8 a second pressure sensor positioned between the proximal end and the  
9 occluding for measuring a pressure on a second side of the occluding  
10 member.

1 28. The catheter of claim 27, further comprising:  
2 a pressure monitor coupled to the first and second pressure sensors,  
3 the pressure monitor determining a pressure difference between the first and  
4 second pressure sensors.

1 29. The catheter of claim 28, further comprising:  
2 an alarm coupled to the pressure monitor for indicating when a  
3 pressure difference sensed by the first and second pressure sensors exceeds a  
4 predetermined threshold.

1 30. The catheter of claim 27, wherein:  
2 the occluding member is a balloon; and  
3 the shaft includes a first lumen, a second lumen and an opening at the  
4 distal end of the shaft fluidly coupled to the first lumen, the second lumen  
5 being fluidly coupled to the balloon for inflating the balloon.

1 31. The catheter of claim 30, further comprising:  
2 means for adjusting the pressure on at least one of the first and second  
3 sides of the balloon when a pressure difference sensed by the first and second  
4 pressure sensors exceeds a predetermined threshold, the pressure adjusting  
5 means reducing the pressure difference to a value below the predetermined  
6 threshold.

1 32. The catheter of claim 31, wherein:  
2 the pressure adjusting means is coupled to the first lumen for adjusting  
3 a fluid pressure exerted by fluid delivered into the ascending aorta through  
4 the first lumen.

1 33. A method of anchoring an occluding member in an ascending aorta of  
2 a patient, comprising the steps of:  
3 inserting a catheter into a patient, the catheter including a shaft having  
4 an occluding member at a distal end, the occluding member having a  
5 collapsed shape and an expanded shape;  
6 positioning the catheter in the patient's ascending aorta;  
7 expanding the occluding member to the expanded shape after the  
8 positioning step to thereby occlude the ascending aorta; and

9 displacing the shaft of the catheter a first amount after the expanding  
10 step so that a predetermined portion of the catheter contacts the patient's  
11 aortic lumen for anchoring the occluding member in the ascending aorta.

1 34. The method of claim 33, wherein:  
2 the displacing step is carried out by withdrawing an amount of the  
3 catheter from the patient so that the predetermined portion of the catheter  
4 engages a radially inner portion of the patient's ascending aorta.

1 35. The method of claim 33, further comprising the step of:  
2 displacing the catheter a second amount in a direction opposite to the  
3 first amount so that a second predetermined portion of the shaft engages a  
4 radially outer wall of the patient's ascending aorta.

1 36. The method of claim 33, further comprising the step of:  
2 inserting the shaft through a delivery cannula, the delivery cannula  
3 having a shaft engaging mechanism and a shaft displacing mechanism;  
4 the displacing step being performed with the shaft displacing  
5 mechanism of the delivery cannula.

1 37. A catheter having an expandable member for occluding an ascending  
2 aorta in a patient, comprising:  
3 a shaft having a longitudinal axis, a distal end, a proximal end, a first  
4 lumen and an opening at the distal end in fluid communication with the  
5 opening, the opening being configured for delivery of a fluid into the  
6 patient's ascending aorta;

7 an expandable member mounted near the distal end of the shaft, the  
8 expandable member having an expanded shape and a collapsed shape, the  
9 expanded shape being configured to occlude the patient's ascending aorta;  
10 and



11 a delivery cannula, the shaft being movably coupled to the delivery  
12 cannula for movement in a direction parallel to the longitudinal axis in an  
13 inward direction and an outward direction;

14 the shaft having a first portion configured to contact the radially inner  
15 wall of the aortic lumen when the shaft is slidably displaced in the outward  
16 direction.

1 38. The catheter of claim 37, further comprising:

2 a shaft displacing mechanism coupled to the delivery cannula, the shaft  
3 displacing mechanism being configured to displace the shaft a predetermined  
4 amount in the outward direction so that the first portion engages the radially  
5 inner wall of the aortic lumen.

1 39. The catheter of claim 37, wherein:

2 the shaft includes a second portion configured to contact a radially  
3 outer wall of the aortic lumen when the shaft is slidably displaced in the  
4 inward direction.

1 40. The catheter of claim 39, wherein:

2 the shaft includes a third portion configured to contact the radially  
3 outer wall of the aortic lumen when the shaft is slidably displaced in the  
4 inward direction, the second portion being positioned between the first and  
5 second portions.

1 41. The catheter of claim 37, wherein:

2 the delivery cannula includes a lumen for introducing a fluid into the  
3 patient.

1 42. The catheter of claim 37, wherein:

2 the shaft includes a first bend and a second bend, the first portion  
3 being positioned between the first and second bends.

1 43. A method of anchoring an occluding member in a patient comprising  
2 the steps of:  
3 inserting a catheter into a patient, the catheter having an occluding  
4 member mounted thereto;  
5 positioning the occluding member at a desired location;  
6 expanding the occluding member to occlude the desired location; and  
7 clamping a portion of the passageway adjacent the desired location to  
8 prevent migration of the occluding member.

1 44. The method of claim 43, wherein:  
2 the inserting step is carried out with the occluding member being a  
3 balloon.

1 45. The method of claim 43, wherein:  
2 the clamping step is carried out by clamping the body passageway  
3 around the balloon thereby trapping the balloon.

1 46. The method of claim 43, wherein:  
2 the inserting step is carried out with the balloon having an indentation;  
3 and  
4 the clamping step is carried out with the clamp being positioned  
5 around the indentation.

1 47. A method of anchoring an occluding member in a patient's ascending  
2 aorta comprising the steps of:  
3 inserting an occluding member in the ascending aorta between the  
4 coronary ostia and the brachiocephalic artery;  
5 expanding the occluding member in the patient after the inserting step;  
6 positioning an anchor in the brachiocephalic artery, the anchor having  
7 a proximal end extending into the aorta, the anchor preventing migration of  
8 the occluding member beyond the brachiocephalic artery.

1 48. The method of claim 47, wherein:  
2 the positioning step is carried out with the anchor being a perfusion  
3 catheter configured to deliver oxygenated blood to the brachiocephalic artery.

1 49. The method of claim 47, wherein:  
2 the anchor is separate from the catheter.

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000